



**SKU:** GBL-4

**UPC:** 0783669960051

**Features & Benefits:**

**Description:** Aluminum Lay-in Ground Lug, Dual Rated, Conductor Range 4-14, Tin Plated, UL

## Specs

### Additional Class Attributes

|                              |            |
|------------------------------|------------|
| Connection                   | Mechanical |
| Mounting Hole Type           | Thru       |
| Mounting Kit Hardware Part # | GBL-MHU    |
| Number of Conductors         | 1          |
| Number of Mounting Holes     | 1          |
| Number of Ports / Wireways   | 1          |
| Wire Orientation             | NA         |

### Dimensions

|                              |         |
|------------------------------|---------|
| Dimension G (IN)             | 0.2     |
| Dimension G (mm)             | 5.08    |
| Drive Size Main              | NA      |
| Drive Type Main              | Slotted |
| Height (IN)                  | 0.79    |
| Height BX (IN)               | 3.125   |
| Height (mm)                  | 20.066  |
| Length (IN)                  | 1.1     |
| Length (mm)                  | 27.94   |
| Mounting Bolt/Stud Size (mm) | 254     |
| Mounting Hole Diameter (IN)  | 0.218   |
| Mounting Hole Diameter (mm)  | 5.5372  |
| Tang Length (IN)             | 0.48    |
| Tang Length (mm)             | 12.192  |
| Tang Thickness (IN)          | 0.12    |
| Tang Thickness (mm)          | 3.048   |
| Tang Width (IN)              | 0.385   |
| Tang Width (mm)              | 9.779   |
| Weight (LB)                  | 0.024   |
| Weight BX (LB)               | 2.623   |
| Width (IN)                   | 0.385   |
| Width BX (IN)                | 3.875   |
| Width (mm)                   | 9.779   |

### Material and Finish

|                            |                               |
|----------------------------|-------------------------------|
| Clamping Hardware Finish   | Zinc Clear Trivalent Chromate |
| Clamping Hardware Material | Steel                         |
| Conductor Material         | Aluminum                      |

|                                |                               |
|--------------------------------|-------------------------------|
| Connector Finish               | Tin                           |
| Insulation                     | NA                            |
| Material                       | Aluminum                      |
| Wire Binding Hardware Finish   | Zinc Clear Trivalent Chromate |
| Wire Binding Hardware Material | Steel                         |

### Additional Technical Specifications

|                |          |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

### Bolt and Screw Sizes

|                                        |            |
|----------------------------------------|------------|
| Clamping Bolt Size                     | 1/4-28     |
| Mounting Bolt/Stud Size                | #10        |
| Number of Wire Binding Screws per Port | 1          |
| Wire Binding Screw Size                | 1/4        |
| Wire Binding Torque                    | 8 AWG = 25 |

### General

|                             |                  |
|-----------------------------|------------------|
| Bag Quantity                | 1                |
| Carton Quantity Description | STD PACK QTY 100 |
| Direct Burial               | Yes              |
| Dual Rated                  | Yes              |
| NEMA Code                   | S-573-2          |
| UPC Code                    | 78366996005      |

### Testing Standards

|                          |                                                                                                                     |
|--------------------------|---------------------------------------------------------------------------------------------------------------------|
| CSA File Number          | LR-29601                                                                                                            |
| CSA Standard             | C22.2 No. 65-03                                                                                                     |
| Prop65 Compliance        | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| ROHS Indicator           | COM                                                                                                                 |
| UL Control Number        | 667P                                                                                                                |
| UL / CULUS Specification | UL 486A/B Listed                                                                                                    |
| UL File Number           | E6207                                                                                                               |

### Color

|       |        |
|-------|--------|
| Color | Silver |
|-------|--------|

### Conductor Ranges

|                                                        |                 |
|--------------------------------------------------------|-----------------|
| Conductor Range AL Solid (Secondary, tap, load)        | NA              |
| Conductor Range AL Stranded (Primary, run, main, line) | 4 Str - 14 Str  |
| Conductor Range AL Stranded (Secondary, tap, load)     | NA              |
| Conductor Range CU Solid (Primary, run, main, line)    | 10 Sol - 14 Sol |
| Conductor Range CU Solid (Secondary, tap, load)        | NA              |
| Conductor Range CU Stranded (Primary, run, main, line) | 4 Str - 14 Str  |
| Conductor Range CU Stranded (Secondary, tap, load)     | NA              |
| Conductor Range AL Solid (Primary, run, main, line)    | 10 Sol - 14 Sol |