



1 polo



2 polos



3 polos

INTERRUPTORES DERIVADOS PARA C.CARGA Y TABLEROS DE ALUMBRADO

Interruptores Termomagnéticos enchufables 3 / 4 " Btplug.

Tensión nominal (V~)	Capacidad Interruptiva Icu (kA)	Corriente nominal In (amperes)	Interruptor			Calibre del conductor máx. admisible
			1 polo	2 polos	3 polos	
120/240	10					
		10	BTN1/10	BTN2/10	BTN3/10	
		15	BTN1/15	BTN2/15	BTN3/15	(1CXF) 12 - 6 AWG Cu
		20	BTN1/20	BTN2/20	BTN3/20	
		30	BTN1/30	BTN2/30	BTN3/30	
		40	BTN1/40	BTN2/40	BTN3/40	
		50	BTN1/50	BTN2/50	BTN3/50	(1CXF) 10 - 1/0 AWG Cu
		60	BTN1/60	BTN2/60	BTN3/60	
		70	-	BTN2/70	BTN3/70	



nuevo

Interruptores falla a tierra Btplug.

Código	Polos	In (A)	I Δn (mA)
BTP1C15R6	1	15	6
BTP1C20R6	1	20	6
BTP1C30R6	1	30	6